N 70, Built-in oven, 60 x 60 cm, Stainless steel B27CR22N1B













Z11AB15A0 Baking tray, non-stick ceramic coated

Z11CG10X0 Barbecue-Set

Z11CR10X0 Baking and roasting grid (standard)

Z11SZ00X0 SeamlessCombination mounting kit

Z11TC10X0 ComfortFlex Rail (1 level)

Z11TC16X0 ComfortFlex Rail (1 level) and racks

Z12CB10A0 Baking tray, anthracite enamelled

Z12CM10A0 Moussaka pan, anthracite enamelled

Z12CQ10A0 Grill tray, anthracite enamelled

Z1913X0 Baking Stone

Built-in oven with CircoTherm® - The award-winning hot air system from Neff

- $\sqrt{\mbox{CircoTherm}^{\mbox{\scriptsize @}}}$ Smart hot-air solution that lets you bake on up to four levels.
- $\sqrt{\,}$ Dual cleaning options: Pyrolytic cleaning programmes just let the oven interior clean itself. EasyClean - the quick and easy option for day to day maintenance.
- $\sqrt{\ }$ Shift Control fast navigation through menus and simple operation with the TFT display.

Technical Data

Color / Material Front : Stainless steel

Construction type: Built-in

Integrated Cleaning system : Pyrolytic+Hydrolytic

Required niche size for installation (HxWxD) : $585-595 \times 560-568 \times 10^{-2}$

550 mm

Dimensions: 595 x 596 x 548 mm

Dimensions of the packed product (HxWxD) : $670 \times 680 \times 670$ mm

Control Panel Material: Stainless steel

Door Material: Glass Net weight: 37.772 kg Usable volume of cavity: 71 |

Cooking method: 4D Hotair, Bottom heat, Bread Baking Setting, Conventional heat, Dough proving setting, Full width grill, Half width grill, Hot Air-Eco, Hot air grilling, low temperature cooking, Pizza

setting

Oven control: electronic Number of interior lights: 1 Approval certificates : CE, VDE

Length of electrical supply cord: 120 cm

EAN code: 4242004197287 Number of cavities (2010/30/EC): 1 Energy efficiency rating: A+

Energy consumption per cycle conventional (2010/30/EC): 0.87

kWh/cycle

Energy consumption per cycle forced air convection (2010/30/EC) :

0.69 kWh/cycle

Energy efficiency index (2010/30/EC): 81.2 %

Connection rating: 2990 W Fuse protection: 13 A Voltage: 220-240 V Frequency: 50; 60 Hz Plug type: no plug





Features

Design

- 2.5" TFT colour display
- Cavity inner surface: enamel anthracite
- Illuminated Shift Control
- Bar handle
- We recommend you to choose complementary products within N70, in order to assure an optimal design combination of your Built-In appliances.

Features

- Door lock during pyrolytic cleaning Control panel lock Automatic safety switch off Residual heat indicator Start button Door contact switch
- Temperature proposal Actual temperature display Heating up indicator
- Interior halogen light, On/off button
- Electronic clock timer
- 4 shelf positions

Cleaning

- Pyrolytic cleaning
- EasyClean
- Full glass inner door

Programmes/functions

- Oven with 12 main functions heating methods: CircoTherm[®], CircoTherm[®] Gentle, Top/bottom heat, Conventional heat Gentle, Circo-roasting, Full surface grill, Centre surface grill, CircoTherm[®] intensive, Bread baking, Bottom heat, Low temperature cooking, Dough proving
- Rapid heat
- Cooling fan

Accessories

• 2 x combination grid, 1 x universal pan

Performance/technical information

Energy efficiency rating (acc. EU Nr. 65/2014): A+
Energy consumption per cycle in conventional mode: 0.87 kWh
Energy consumption per cycle in fan-forced convection mode: 0.69 kWh


Number of cavities: Main cavity Heat source: electrical Cavity volume: 71 litre

- Total connected load electric: 2.99 KW
- Temperature range 40 °C 200 °C
- 120 cm Cable length
- Nominal voltage: 220 240 V
- Appliance dimension (hxwxd): 595 mm x 596 mm x 548 mm
- Niche dimension (hxwxd): 585 mm - 595 mm x 560 mm - 568 mm x 550 mm
- Please refer to the dimensions provided in the installation manual



COOKING PASSION SINCE 1877

Dimensioned drawings



If the appliance will be installed underneath a hob, the following worktop thicknesses (including substructure if necessary) must be taken into account.

Hob type	min. worktop thickness	
	fitted	flush
Induction hob	37 mm	38 mm
Full surface Induction hob	47 mm	48 mm
Gas hob	30 mm	38 mm
Electric hob	27 mm	30 mm

