
N 70, Built-in oven with added steam function, $60 \times 60 \text{ cm}$, Stainless steel

B57VR22N0B





- $\sqrt{\,}$ Slide&Hide® unrestricted access in the oven interior and easy handling due to rotating handle
- $\sqrt{}$ Dual cleaning options: Pyrolytic cleaning programmes just let the oven interior clean itself. EasyClean the quick and easy option for day to day maintenance.
- √ Shift Control fast navigation through menus and simple operation with the TFT display.
- $\sqrt{\mbox{ LED lights}}$ Bright illumination exactly where you need it.













Optional accessories

Z11AB15A0: Baking tray, non-stick ceramic coated, Z11CG10X0: Barbecue-Set, Z11CR10X0: Baking and roasting grid (standard), Z11SZ00X0: SeamlessCombination mounting kit, Z11SZ80X0: SeamlessCombination 60 + 29cm, Z11SZ90X0: SeamlessCombination 60 + 45cm, Z11TC10X0: ComfortFlex Rail (1 level), Z11TC16X0: ComfortFlex Rail (1 level) and racks, Z12CB10A0: Baking tray, anthracite enamelled, Z12CM10A0: Moussaka pan, anthracite enamelled, Z12CQ10A0: Grill tray, anthracite enamelled, Z1913X0: Baking Stone

Features

Technical Data

Color / Material Front : Stainless steel

Construction type: Built-in

Integrated Cleaning system: Pyrolytic+Hydrolytic

Required niche size for installation (HxWxD) : $585-595 \times 560-568 \times 10^{-2}$

550 mm

Dimensions : 595 x 596 x 548 mm

Dimensions of the packed product (HxWxD) : 675 x 690 x 660 mm

Control Panel Material : Stainless steel

Door Material : Glass Net weight : 43.271 kg Usable volume of cavity : 71 l

Cooking method: 4D Hotair, Bottom heat, Bread Baking Setting, Conventional heat, Full width grill, Half width grill, Hot Air-Eco, Hot air

grilling, low temperature cooking, Pizza setting, warming

Oven control : electronic Number of interior lights : 1 Approval certificates : CE, VDE

Length of electrical supply cord: 120 cm

EAN code: 4242004181965 Number of cavities (2010/30/EC): 1 Energy efficiency rating: A+

Energy consumption per cycle conventional (2010/30/EC): 0.87

kWh/cycle

Energy consumption per cycle forced air convection (2010/30/EC):

0.69 kWh/cycle

Energy efficiency index (2010/30/EC) : 81.2 $\,\%$

Connection rating: 3450 W Fuse protection: 16 A Voltage: 220-240 V Frequency: 60; 50 Hz Plug type: no plug





N 70, Built-in oven with added steam function, 60 x 60 cm, Stainless steel B57VR22N0B

COOKING PASSION SINCE 1877

Design

- 2.5" TFT colour display
- Cavity inner surface: enamel anthracite
- Illuminated Shift Control
- Slide&Hide® with rotating handle
- We recommend you to choose complementary products within N70, in order to assure an optimal design combination of your Built-In appliances.

Features

- Door lock during pyrolytic cleaning Control panel lock Automatic safety switch off Residual heat indicator Start button Door contact switch
- Temperature proposal Actual temperature display Heating up indicator automatic programmes:
- Automatic programmes
- LED light, On/off button
- Water tank empty indicator
- Electronic clock timer
- 4 shelf positions

Cleaning

- Pyrolytic cleaning
- EasyClean
- Full glass inner door

Programmes/functions

- Oven with 12 main functions heating methods: CircoTherm®, CircoTherm® Gentle, Top/bottom heat, Conventional heat Gentle, Circo-roasting, Full surface grill, Centre surface grill, CircoTherm® intensive, Bread baking, Bottom heat, Low temperature cooking, Keep warm
- Additional heating methods with steam: Reheat with steam, Dough proving
- Additional functions: De-scaling programme Drying function steam cooking function
- Number of automatic programmes: 14 PC
- Rapid heat
- Cooling fan

Accessories

• 1 x universal pan, 2 x combination grid

Performance/technical information


• Energy efficiency rating (acc. EU Nr. 65/2014): A+ Energy consumption per cycle in conventional mode: 0.87 kWh Energy consumption per cycle in fan-forced convection mode: 0.69 kWh


Number of cavities: Main cavity Heat source: electrical Cavity volume: 71 litre

- 1 | Water tank capacity
- Location of water tank: Outside cavity
- Total connected load electric: 3.45 KW
- 120 cm Cable length
- Nominal voltage: 220 240 V
- Appliance dimension (hxwxd): 595 mm x 596 mm x 548 mm
- Niche dimension (hxwxd): 585 mm 595 mm x 560 mm 568 mm x 550 mm
- Please refer to the dimensions provided in the installation manual



N 70, Built-in oven with added steam function, 60 x 60 cm, Stainless steel B57VR22N0B





If the appliance will be installed underneath a hob, the following worktop thicknesses (including substructure if necessary) must be taken into account.

Hob type	min. worktop thickness	
	fitted	flush
Induction hob	37 mm	38 mm
Full surface Induction hob	47 mm	48 mm
Gas hob	30 mm	38 mm
Electric hob	27 mm	30 mm

