N 50, Built-in oven with added steam function, 60×60 cm, Stainless steel

B5AVH6AH0B





Α









Optional accessories

Z11AB15A0 Baking tray, non-stick ceramic coated

Z11CB10E0 Baking tray, grey enamelled

Z11CR10X0 Baking and roasting grid (standard)

Z11TF36X0 3 level telescopic rails, full ext

Z11TI15X0 Cliprails

Z12CQ10A0 Grill tray, anthracite enamelled

Z1913X0 Baking Stone

Built-in oven with Added Steam and Slide&Hide® - a gentle touch is enough to add steam and to have unrestricted access to the oven interior thanks to the fully retracting oven door with rotating handle

- $\sqrt{\,}$ Slide&Hide® The fully disappearing oven door with rotating handle.
- $\sqrt{\rm CircoTherm^{\odot}}$ Smart hot-air solution that lets you bake on up to three levels at once.
- $\sqrt{}$ Pyrolytic Self-Cleaning Let the oven clean itself.
- $\sqrt{\,}$ LCD-Display simple, straightforward with large characters for clear reading
- $\sqrt{}$ Home Connect Unleash your creativity via app.

Feature

Technical Data

Color / Material Front : Stainless steel

Construction type : Built-in

Integrated Cleaning system: Pyrolytic

Required niche size for installation (HxWxD) : $585-595 \times 560-568 \times 10^{-2}$

550 mm

Dimensions : 595 x 594 x 548 mm

Dimensions of the packed product (HxWxD) : $660 \times 690 \times 660 \,$ mm

Control Panel Material : Glass Door Material : Glass Net weight : 40.524 kg Usable volume of cavity : 71 l

Cooking method: Bread Baking Setting, Conventional heat, Full width

grill, Hot Air, Hotair gentle, Hot air grilling, Pizza setting

First cavity material : Other Oven control : electronic Number of interior lights : 1 Approval certificates : CE, VDE

Length of electrical supply cord: 120 cm

EAN code: 4242004243588 Number of cavities (2010/30/EC): 1 Energy efficiency rating: A

Energy consumption per cycle conventional (2010/30/EC) : 1.04

kWh/cvcle

Energy consumption per cycle forced air convection (2010/30/EC) :

0.81 kWh/cycle

Energy efficiency index (2010/30/EC) : 95.3 $\,\%$

Connection rating : 3600 W Fuse protection : 16 A Voltage : 220-240 V Frequency : 50; 60 Hz Pluq type : no pluq





N 50, Built-in oven with added steam function, 60 x 60 cm, Stainless steel B5AVH6AH0B

Features

Design

- LCD-Display Control (white)
- Cavity inner surface: enamel grey
- 4 shelf positions
- Elongated designed dials, Retractable control dials, Bevelled oval controls
- Slide&Hide® with rotating handle

Features

- Electronic clock timer
- Automatic programmes
- HomeConnect ready on WLAN
- Door lock during pyrolytic cleaning Control panel lock Automatic safety switch off Residual heat indicator Door contact switch
- Temperature proposal
 Actual temperature display
 Heating up indicator
 automatic programmes:
 Automatic start
- Interior halogen light, On/off button
- Water tank capacity with a volume of 220ml
- Location of water tank: Outside cavity

Cleaning

- Pyrolytic cleaning
- Full glass inner door

Programmes/functions

- Oven with 8 heating methods: CircoTherm®, Top/bottom heat, Circo-roasting, Full surface grill, CircoTherm® intensive, Bread baking, CircoTherm® gentle, Reheat with steam
- Heating modes in combination with steam function: CircoTherm[®], Circo-roasting, Top/bottom heat
- Additional functions: De-scaling programme
- Number of automatic programmes: 15
- Rapid heat
- Cooling fan

Accessories

• 2 x combination grid, 1 x universal pan

Performance/technical information

Energy efficiency rating (acc. EU Nr. 65/2014): A
 Energy consumption per cycle in conventional mode: 1.04 kWh
 Energy consumption per cycle in fan-forced convection mode: 0.81 kWh

Number of cavities: Main cavity Heat source: electrical Cavity volume: 71 litre


- Total connected load electric: 3.6 KW
- 120 cm Cable length
- Nominal voltage: 220 240 V
- Appliance dimension (hxwxd): 595 mm x 594 mm x 548 mm
- Niche dimension (hxwxd): 585 mm 595 mm x 560 mm 568 mm x 550 mm
- Please refer to the dimensions provided in the installation manual




N 50, Built-in oven with added steam function, 60 x 60 cm, Stainless steel B5AVH6AH0B





Dimensioned drawings



A: 19.5 mm B: Space for appliance connection 320 x 115 mm







If the appliance will be installed underneath a hob, the following worktop thicknesses (including substructure if necessary) must be taken into account.

Hob type	min. worktop thickness	
	fitted	flush
Induction hob	37 mm	38 mm
Full surface Induction hob	47 mm	48 mm
Gas hob	30 mm	38 mm
Electric hob	27 mm	30 mm