

N 70, Wall-mounted cooker hood, 90 cm, clear glass black printed  
D95FRM1S0B



COOKING PASSION SINCE 1877



The Creative Slimline hood does not only offer high-performance but is also magnetic, can be written on and can be used as a bookshelf

- ✓ Efficient Drive Motor – Quiet and energy-efficient hood motor for a calmer kitchen.
- ✓ TouchControl: thanks to the integrated flat surface of the control panel, adjustments can be easily made with just one finger
- ✓ Intensive speed setting: increases the extraction rate when the steam gets intense
- ✓ LED Lighting – Clear illumination while you cook.

#### Features

##### Technical Data

Typology : Wall-mounted  
Approval certificates : CE, E17D UKCA marking, VDE  
Length of electrical supply cord : 130 cm  
Height of product, without chimney : 430 mm  
Minimum distance above an electric hob : 450 mm  
Net weight : 23.872 kg  
Type of control : Electronic  
Maximum output air extraction : 405 m<sup>3</sup>/h  
Boost position output recirculating : 404 m<sup>3</sup>/h  
Maximum output recirculating air : 249 m<sup>3</sup>/h  
Boost position air extraction : 739 m<sup>3</sup>/h  
Number of lights (Stck) : 2  
Noise level : 58 dB(A) re 1 pW  
Diameter of air outlet : 120 / 150 mm  
Grease filter material : Washable aluminium  
EAN code : 4242004210177  
Connection rating : 143 W  
Fuse protection : 10 A  
Voltage : 220-240 V  
Frequency : 60; 50 Hz  
Plug type : GB plug  
Installation type : Wall-mounted



4 242004 210177

#### Optional accessories

Z51AF1X6 Clean Air Plus recirculation kit  
Z51AFR0X0 Long Life recirculation kit (chimless)  
Z51AFS0X0 Long Life recirculation kit  
Z51AFV1X6 Clean Air Plus recirc. kit (chimless)  
Z51AXK0N0 Chimney extension 1000 mm  
Z51AXL0N0 Chimney extension 1500 mm  
Z53XXB1X6 Clean Air Plus odor filter (replacement)  
Z91AXE1S1 Chimney standard black

*N 70, Wall-mounted cooker hood, 90 cm, clear  
glass black printed  
D95FRM1SOB*



COOKING PASSION SINCE 1877

## Features

### Key performance features:

- Energy Efficiency Class: A (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 ø 15 cm:  
max. Normal use 404 m<sup>3</sup>/h  
Intensive 739 m<sup>3</sup>/h
- Noise max. Normal Level: Noise, max. speed in normal us: 58 dB dB\*

### Features

- Touch control
- LED display
- 3 speeds plus intensive
- 2 x 1.5w LED Light
- Colour Temperature: 3500 K
- Automatic intensive revert (6mins)
- 2 metal grease filter cassettes
- easy to clean Inner frame
- Installation: wall
- Rim ventilation

### Design

- Chimney hood
- Electronic controls

### Performance/technical information

- Installation with gas hob not recommended
- Suitable for ducted extraction and recirculation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Installation system: Wall fixing inclined/flat/cube
- Extraction rate according to EN 61591 max. 739 m<sup>3</sup>/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 58 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:  
Max. normal use: 58 dB(A) re 1 pW  
Intensive: 71 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 58 dB (A) re 1pW
- Power rating: 143 W
- Light Intensity: 225 lux
- Electrical cable length 1.3 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 981-1251 x 890 x 362 mm
- Dimensions recirculating (HxWxD): 1041-1311 x 890 x 362 mm
- Dimensions recirculating with CleanAir module (HxWxD):  
1171 x 890 x 362 mm - mounting with outer chimney  
1241-1511 x 890 x 362 mm - mounting with telescopic chimney
- Blower Efficiency Class: B\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: B\*
- Average Energy Consumption: 39 kWh/year\*

### Optional accessories

- Recirculating kit Z50XXPOX0

\* In accordance with the EU-Regulation No 65/2014

N 70, Wall-mounted cooker hood, 90 cm, clear  
glass black printed  
D95FRM1SOB

## Dimensioned drawings

