

Serie | 6, Free-standing fridge-freezer with freezer at bottom, 204 x 60 cm, Inox-easyclean KGN39HIEP









Included accessories

3 x egg tray 1 x ice cube tray

Optional accessories

KSZ39AL00 : Connection set inox

NoFrost bottomfreezer : no need to defrost your freezer

- **Home Connect:** home appliances with smart connectivity for an easier everyday life.
- VitaFresh: keeps food fresh for longer in climate controlled drawers at near 0°C.
- Perfect Fit: place your fridge right next to walls and other appliances to save space.
- LED lights bring a completely new lighting concept to fridges
- Automatic super freezing: for freezing smaller food loads faster whilst protecting your frozen items from defrosting, thanks to the detection of temperature increase

Technical Data

A ↑ G

Energy Efficiency Class: E

Average annual energy consumption in kilowatt hour per year

(kWh/a): 238 kWh/annum

Sum of volume of frozen compartments: 89 I Sum of volume of chill compartments: 279 I

Airborne acoustical noise emissions : 39 dB(A) re 1 pW

Airborne acoustical noise emission class: C

Construction type: Free-standing Door panel options: Not possible Width of the appliance: 600 mm Depth of the product: 660 mm Net weight: 79.978 kg

Connection rating: 100 W Fuse protection: 10 A Door hinge: Right Voltage: 220-240 V Frequency: 50 Hz

Approval certificates: CE, VDE

Length of electrical supply cord: 240 cm

Storage Period in Event of Power Failure (h): 13 h

Number of compressors: 1

Number of independent cooling systems: 2

Interior ventilator: No Reversible Door Hinge: No

Number of Adjustable Shelves in fridge compartment (Stck): 3

Shelves for Bottles: Yes Installation type: N/A





Serie | 6, Free-standing fridge-freezer with freezer at bottom, 204 x 60 cm, Inox-easyclean KGN39HIEP

NoFrost bottomfreezer : no need to defrost your freezer

Design features

- Wi-Fi connectivity
- Stainless Steel EasyClean doors and Pearl grey (VZF 07127) side panels
- Vertical door handle
- Right hinged door
- Electronic control (external in-door LCD display)

Food freshness system

 Two separate cooling circuits allow independent temperature control and prevents the transference of humidity between the fridge and freezer cavity

Key features - Fridge section

- 1 VitaFresh Plus drawer with humidity control. Fruit and vegetables retain vitamins and last longer.
 2 VitaFresh plus ◀0°C▶ drawers with temperature control on an Easy Access Drawer Fish and meat stay fresh for longer
- MultiAirflow system improves circulation of air around the fridge
- Bright interior LED fridge light
- 5 safety glass shelves (3 height adjustable)
- Door shelves in fridge door: 1 large and 2 small.
- Super Cooling: automatic deactivation
- Metal bottle rack

Key features - Freezer section

- No Frost, never have to defrost ever again
- 3 freezer drawers
- SuperFreeze function with automatic deactiviation
- Calendar frozen food
- Freezer malfunction warning signal: optical and acoustical warning system

Additional features

- Optical and accoustical
- 3 x egg tray, 1 x ice cube tray

Dimension and installation

- Connection value 100 W
- 220 240 V
- Height adjustable front feet
- Dimensions: 204 cm H x 60 cm W x 66 cm D
- Based on the results of the standard 24-hour test. Actual consumption depends on usage/position of the appliance.
- To achieve the declared energy consumption, the distanceholders have to be used. As a result, the appliance depth increases by about 3.5 cm. The appliance used without the distance holder is fully functional, but has a slightly higher energy consumption.

Performance and Consumption

- EU19_EEK_D: E

- Total Volume: 368 I

- Net Fridge Volume : 279 l

- Net Freezer Volume : 89 l

- Freezing capacity 24h: 10 kg

- Annual Energy Consumption: 238 kWh/a

- Climate Class: SN-T


- EU19_Fast freezer facility_D

- Noise Level: 39 dB, EU19_Noise emission class_D: C


- Temperature rise time : EU19_Temperature rise time_D: 13 H



Serie | 6, Free-standing fridge-freezer with freezer at bottom, 204 x 60 cm, Inoxeasyclean KGN39HIEP



If the appliance is fitted directly to the wall, all of the drawers can be pulled out fully. * With and without external handle.



In models with vertical integrated handles, in order to open easily, a minimum distance of 65 mm is needed.

measurements in mm