
# N 70, Gas hob, 60 cm, Stainless steel T26DA59N0









The gas hob with a stainless-steel surface design, slightly raised glass surface and adjustable FlameSelect

- $\sqrt{\mbox{ FlameSelect}^{\mbox{\scriptsize @}}}$  Gain ultimate control of your flame.
- $\sqrt{\,$  7-Segment Display with Residual Heat Indicator a digital display showing the remaining heat.
- $\sqrt{\ }$  Pan Supports continuous cast-iron pan supports for maximum stability and cooking convenience.
- $\sqrt{}$  Wok Burner powerful cooking at up to 3.5 kW.
- $\sqrt{\,}$  Sword Knobs a better feel and easier to operate, the new knob in an attractive design.

### Features

#### Technical Data

Product name/family: gas hob w integrated controls

Construction type : Built-in

Energy input: Gas

Total number of positions that can be used at the same time: 4

Type of control setting devices: sword knobs

Required niche size for installation (HxWxD) : 45 x 560-562 x

480-492 mm

Width of the appliance : 582 mm Dimensions :  $45 \times 582 \times 520 \text{ mm}$ 

Dimensions of the packed product (HxWxD) :  $141 \times 651 \times 578 \text{ mm}$ 

Net weight : 11.631 kg Gross weight : 12.5 kg

Residual heat indicator : Separate Location of control panel : Hob front Basic surface material : Stainless steel Color of surface : Stainless steel Color of frame : Stainless steel Approval certificates : CE, Eurasian Length of electrical supply cord : 100 cm

EAN code : 4242004179177 Electrical connection rating : 2 W Gas connection rating : 8000 W

Fuse protection : 3 A Voltage : 220-240 V Frequency : 50; 60 Hz





#### Features

#### Design

- Stainless steel surface
- black cast iron pan supports with protective rubber feet

#### Usage convenience

- FlameSelect with 9 steps: precisely control and adjust the flame in nine defined levels.
- LED display for each zone: see the selected power level and the residual heat.
- Design co-ordinated control dials: easily access dials in front with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

#### Burners and power

- 4 burner hob
- Left front: Standard burner up to 1.75 KW (depending on gas type)
- Left rear: Standard burner up to 1.75 KW (depending on gas type)
- Right rear: WOK burner up to 3.5 KW (depending on gas type)
- Right front: Economy burner up to 1 KW (depending on gas type)

## Safety

- Flame failure safety device: prevents unwanted gas flow when flame goes out.
- 2-stage residual heat indicators: indicates which burner parts and pan supports are still hot.

## Installation (gas types & measurements)

- Usable for: Nat gas L/LL G25/20mbar(DE) NG H/E 20mbar, E+ 20/25mbar Natural gas H 25 mbar (HU) Natural gas L 25 mbar (NL) Liquid gas G30,31 28-30/37mbar Liquid gas G30 37 mbar (PL)
- Factory set for connection to mains gas
- Nozzle set for LPG jets (28-30/37mbar) included. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- Dimensions of the product (HxWxD mm): 53 x 582 x 520
- Required niche size for installation (HxWxD mm): 45 x 560 x (480 492)
- Min. worktop thickness: 30 mm
- Power cord: 1 m
- Connected load: 8 KW

Liquid gas 50 mbar



